



KUIPER
HOLLAND

PRODUCT DATA SHEET



KUIPER BASIC POPLAR PLYWOOD

DIMENSION: 251 X 126 CM

WEIGHT: 420 KG/M³

THICKNESS: 3-3.2-3.6-4-5-6-8-9-10-11
12-14-15-16-17-18-22-25 MM

Panel with core and faces made of poplar from controlled and sustainable European plantations. It has many applications thanks to its excellent attributes.

All products of the Efficiency family stand out for their exceptional properties: lightweight, surface quality, easy-to-machine and easy-to-transport, thanks to their poplar cores and faces.

Glue Type: Class 1 or Class 3 (EN 314-2).

Emission: E1, according to the rule EN 717-2. This product can be made on demand according to the ARB standards (low formaldehyde emissions).

Grades: Faces grades B/BB/C.

Applications/Uses:

- Decorative coverings for walls, ceilings, façades, interior partitions, paneling...
- Semi-structural uses in roof paneling, sandwich panels
- Furniture industry
- Toys, marquetry, DIY...




Technical features

	Values	Standard
Density (kg/m ³)	420-480	UNE EN 323
MOE - Modulus of elasticity (N/mm ²)	3.500-4.800	UNE EN 310
Face Screw Holding (kgf)	135	UNE EN 320
Moisture content (%)	6-14	UNE EN 322

Formats

Dimensions mm.	2500x1220, 2520x1850, 3100x1530, 3100x1850										
Thickness mm.	6	8	10	12	15	18	22	25	30	40	
N° of plies	5	5	5	7	7	7/9	9	11	13	15	

Formats may vary without notice. Please contact your local sales manager to check the availability in your region.

CE CE2+ CARB 

garnica

Challenge the ordinary